



Shoe & Leather Care Products



Horse Care Products



Footwear finishes, adhesives and craft products

Material Safety Data Sheet

Hazardous Substance, Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: **Joseph Lyddy Dub-N-Shine**

Recommended use: Treatment for waterproofing, softening and preserving boots and leathers.

Supplier: Waproo Pty Ltd
ABN: 80 004 520 254
Street Address: 7 Ordish Road
Dandenong South VIC 3175
Australia
Telephone: + 613 9238 9888
Facsimile: + 613 9238 9899

Emergency telephone number: +613 9238 9888 (8am – 5pm, Monday to Friday)

2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of NOHSC Australia.

Hazard Category:

Xn Harmful

Risk Phrase(s):

R65: Harmful: May cause lung damage if swallowed.

Safety Phrase(s)

S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.

S62: If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail.

Class: 4.1 Flammable Solid

Poisons Schedule (Aust): Not applicable

3. COMPOSITION INFORMATION

CHEMICAL	ENTITY CAS NO.	PROPORTION
Non hazardous ingredients	-	30-60%
Narrow Cut Kerosine	64742-82-1	10-30%

Material Safety Data Sheet

Medium aliphatic petroleum solvent	64742-88-7	10-30%
Light aromatic petroleum solvent	64742-95-6	1-10%
		100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through a facemask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. Seek immediate medical advice.

Skin contact: If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

Eye contact: If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.

Ingestion: Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Get to a doctor or hospital quickly.

Notes to physician: Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Specific hazards: Flammable solid. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.

Fire fighting further advice: If safe to do so, remove containers from path of fire. Keep containers cool with water spray. Can melt and flow in a fire situation. On burning may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Hazchem Code: 1[Z]

Suitable extinguishing media: If material is involved in a fire use water jets, water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours. Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

Material Safety Data Sheet

LARGE SPILLS

Shut off all possible sources of ignition. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Use a spark-free shovel. Collect and seal in properly labeled containers or drums for disposal. If contamination of sewers or waterways has occurred advise local emergency services.

Dangerous Goods – Initial Emergency Response Guide No: 20

7. HANDLING AND STORAGE

Handling: Avoid skin and eye contact and inhalation of vapour.

Storage: Store in a cool, dry, well ventilated place and out of direct sunlight. Store away from incompatible materials described in Section 10. Store away from sources of heat or ignition. Keep containers closed when not in use - check regularly for spills.

This material is classified as a Dangerous Good 4.1 Flammable Solid as per the criteria of the Australian Dangerous Goods Code and must be stored in accordance with the relevant regulations.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits:

No value assigned for this specific material by the National Occupational Health and Safety Commission (NOHSC Australia).

However for:

	TWA		STEL		CARCINOGEN CATEGORY	NOTICES
	ppm	mg/m3	ppm	mg/m3		
Solvent	-	480	-	-	-	-

Recommended by ingredient supplier.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances [NOHSC: 1005 (1994)]" the ingredients in this material do not have a Biological Limit Allocated.

Material Safety Data Sheet

Engineering measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use with local exhaust ventilation or while wearing appropriate respirator. Vapour heavier than air - prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected. Keep containers closed when not in use.

Personal protection equipment: OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES, RESPIRATOR.

Wear overalls, chemical goggles and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form / Colour / Odour: Colourless solid.

Solubility:	Insoluble in water
Specific Gravity (20 °C):	N Av
Relative Vapour Density (air=1):	N Av
Vapour Pressure (20 °C):	N Av
Flash Point (°C):	N Av
Flammability Limits (%):	N Av
Autoignition Temperature (°C):	N Av
Melting Point/Range (°C):	N Av
Boiling Point/Range (°C):	N Av
pH:	N App

(Typical values only - consult specification sheet)

N Av = Not available

N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: No information available.

Conditions to avoid: No information available.

Incompatible Materials: Oxidising agents.

Hazardous decomposition products: No information available.

Hazardous reactions: No information available.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Material Safety Data Sheet

Acute Effects

Inhalation: Material may be irritant to mucous membranes and respiratory tract. Inhalation of vapour can result in headaches, dizziness and possible nausea. Inhalation of high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness.

Skin contact: Contact with skin may result in irritation. Will have a degreasing action on the skin. Repeated or prolonged skin contact may lead to irritant contact dermatitis.

Eye contact: May be an eye irritant.

Ingestion: Swallowing can result in nausea, vomiting and central nervous system depression. If the victim is uncoordinated there is greater likelihood of vomit entering the lungs and causing subsequent complications.

Long Term Effects: No information available for product.

Acute toxicity / Chronic toxicity

No LD50 data available for the product.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Refer to State/Territory Land Waste Management Authority.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail.

UN No:	1325
Dangerous Goods Class:	4.1
Packing Group:	III
Hazchem Code:	1[Z]
Emergency Response Guide No:	20

Proper Shipping Name: FLAMMABLE SOLID, ORGANIC, N.O.S. (contains TURPENTINE SUBSTITUTE)

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1), flammable gases (Class 2.1), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2) or radioactive substances (Class 7), however exemptions may apply.

Material Safety Data Sheet

MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

UN No: 1325
Dangerous Goods Class: 4.1
Packing Group: III

Proper Shipping Name: FLAMMABLE SOLID, ORGANIC, N.O.S. (contains TURPENTINE SUBSTITUTE)

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN No: 1325
Dangerous Goods Class: 4.1
Packing Group: III

Proper Shipping Name: FLAMMABLE SOLID, ORGANIC, N.O.S. (contains TURPENTINE SUBSTITUTE)

15. REGULATORY INFORMATION

Poisons Schedule (Aust): Not applicable

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Literary reference

This Material Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd on behalf of its client.

For further information about this product;

Telephone: +613 9238-9888

Reason(s) For Issue: Admin Changes

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Waproo Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.